WO 2005/061649

8

PCT/NZ2004/000326

<u>Claims</u>

- A resilient compound for use in forming a seal characterised in that the sealing compound includes a detectable material dispersed therethrough.
 - 2. A resilient compound as claimed in claim 1 wherein the detectable material is of a type, which can be detected by x-rays, metal detection or other detection means.

10

25

5

- A resilient compound as claimed in claim 1 or 2 wherein the detectable material is uniformly dispersed through the compound.
- 4. A resilient compound as claimed in any one of claims 1 to 3 wherein the detectable material is barium sulphate.
 - 5. A resilient compound as claimed in claim 4 wherein the barium sulphate is added at the compounding stage of the resilient compound.
- 20 6. A resilient compound as claimed in claim 4 or 5 wherein the barium sulphate constitutes about 5% by volume.
 - A resilient compound as claimed in any one of claims 1 to 6 wherein the sealing compound is principally a natural or synthetic rubber or a thermoplastic material.

WO 2005/061649 PCT/NZ2004/000326

- 8. A resilient compound as claimed in claim 7 wherein the thermoplastic material is a modified polybutyleneterephthate.
- 9. A sealing device made in whole or in part from a resilient compound,5 which includes a detectable material, dispersed therethrough.
 - 10. A sealing device as claimed in claim 9 wherein the detectable material is of a type, which can be detected by x-rays, metal detection or other detection means.

11. A sealing device as claimed in claim 9 or 10 wherein the detectable material is uniformly dispersed through the compound.

10

15

25

- 12. A sealing device as claimed in any one of claims 9 to 12 wherein the detectable material is a barium sulphate.
 - 13. A sealing device as claimed in claim 12 wherein the barium sulphate is added at the compounding stage.
- 20 14. A sealing device as claimed in claim 12 or 13 wherein the barium sulphate constitutes 5% by volume of the resilient compound.
 - 15. A sealing device as claimed in any one of claims 9 to 14 wherein the resilient compound is principally a natural or synthetic rubber or a thermoplastic material.

WO 2005/061649 PCT/NZ2004/000326

- 16. A sealing device as claimed in claim 15 wherein the thermoplastic material is a modified polybutyleneterephthate.
- 17. A sealing device as claimed in any one of claims 9 to 16 when in the form of a dynamic or static "O" ring, sheet gasket, sanitary O ring, butterfly valve seat, lip seal or sanitary valve seat.
 - 18. A resilient compound as claimed in claim 1 substantially as herein described.

19. A sealing device as claimed in claim 9 substantially as herein described.

10